NSN 5305-01-173-3578

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-173-3578 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.338 inches and 0.388 inches **Fastener Length:** Between 0.598 inches and 0.628 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Feat **Surface Finish:** 32.0 microinches threads **Special Features:** Per b-1 engineering Material: Titanium alloy **Material Specification:** Ams 4967 comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:**

80205-nas1580 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-173-3578

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0