
## NSN 5305-01-173-3579

Close Tolerance Screw - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.337 inches and 0.387 inches Fastener Length: Between 0.472 inches and 0.502 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.258 inches and 0.305 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches Internal Drive Style: Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Special Features:** Internal drive ribbed Material: Titanium alloy **Material Specification:** Ams4967 comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1581 professional/industrial association standard Shelf Life: N/a Unit Of Measure:

---

## NSN 5305-01-173-3579

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

