NSN 5305-01-173-3581

Thread Class:

Specification Data:

80205-nas1581 professional/industrial association standard

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-173-3581

| 3a |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.338 inches and 0.388 inches |
| Fastener Length: |
| Between 0.848 inches and 0.878 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.258 inches and 0.305 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.490 inches and 0.510 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 24.0 rockwell c and 35.0 rockwell c |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single |
| material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| 112 |

NSN 5305-01-173-3581

Close Tolerance Screw - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0