## NSN 5305-01-173-3582

Close Tolerance Screw - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5305-01-173-3582

Thread Class:
3a Thread Direction:
Right-hand
Thread Length:
Between 0.378 inches and 0.428 inches
Fastener Length:
Between 1.076 inches and 1.106 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.464 inches and 0.507 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Special Features:
Internal drive ribbed
Material:
Titanium alloy
Material Specification:
Ams4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-173-3582

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

