## NSN 5305-01-173-3587

Close Tolerance Screw - Page 1 of 2





## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.443 inches and 0.510 inches Fastener Length: Between 0.765 inches and 0.812 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.456 inches and 0.508 inches **Head Height:** Between 0.0713 inches and 0.0733 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Special Features:** Furnished with one o-ring Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5305-01-173-3587

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

