NSN 5305-01-173-3593

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-173-3593 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.378 inches and 0.428 inches **Fastener Length:** Between 0.763 inches and 0.793 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.4640 inches and 0.5066 inches **Grip Diameter:** Between 0.2480 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy **Material Specification:** Ams-4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-173-3593

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0