NSN 5305-01-173-3605

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-173-3605

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.313 inches and 0.363 inches
Fastener Length:
Between 0.385 inches and 0.415 inches
Head Style:
Pan
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
Locking Feature:
Pellet threads or strip threads
Grip Diameter:
Between 0.1625 inches and 0.1635 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.164 inches
Grip Length:
Between 0.052 inches and 0.072 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Plastic locking feature
Material Specification:
Ams 5737 assn standard single material response fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response fastener
Thread Series Designator:
Unjc
Specification Data:
80205-pas 1172 professional/industrial association standard

NSN 5305-01-173-3605

Close Tolerance Screw - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0