NSN 5305-01-173-4793

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-173-4793 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.399 inches and 0.417 inches **Fastener Length:** Between 0.852 inches and 0.878 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.543 inches and 0.562 inches **Head Height:** Between 0.244 inches and 0.250 inches **Shoulder Diameter:** 0.371 inches first shoulder and 0.373 inches first shoulder **Shoulder Length:** 0.372 inches first shoulder and 0.378 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl3 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a

NSN 5305-01-173-4793

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0