NSN 5305-01-173-5039

Setscrew - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-173-5039

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.240 inches and 0.260 inches
Head Style:
Headless (setscrew)
Spline Minor Diameter:
0.380 inches
Spline Major Diameter:
Between 0.049 inches and 0.050 inches
Spline Width:
Between 0.016 inches and 0.017 inches
Locking Feature:
Strip threads
Point Style:
Cup
Internal Drive Style:
Four spline
Thread Diameter:
Thread Diameter: 0.080 inches
0.080 inches
0.080 inches Thready Qty Per Inch (tpi):
0.080 inches Thready Qty Per Inch (tpi): 56
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi):
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material:
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel Surface Treatment:
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel Surface Treatment: Passivate
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Thread Series Designator:
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life:
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
0.080 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: