
NSN 5305-01-173-5042

Socket Head Cap Screw - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.346 inches and 1.500 inches

Fastener Length:

Between 1.440 inches and 1.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.735 inches and 0.750 inches

Head Height:

Between 0.492 inches and 0.500 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.500 inches

Width Across Flats:

Between 0.375 inches and 0.379 inches

Thready Qty Per Inch (tpi):

13

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-173-5042

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

