

View Online at <https://aerobasegroup.com/nsn/5305-01-173-5047>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.850 inches and 0.970 inches

**Fastener Length:**

Between 3.215 inches and 3.255 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 1.287 inches and 1.312 inches

**Head Height:**

Between 0.610 inches and 0.625 inches

**Shoulder Diameter:**

0.996 inches first shoulder and 0.998 inches first shoulder

**Shoulder Length:**

2.245 inches first shoulder and 2.255 inches first shoulder

**Single Shear Strength:**

84000 pounds per square inch

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.750 inches

**Width Across Flats:**

0.500 inches

**Thready Qty Per Inch (tpi):**

10

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 43.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2 cl3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0