Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-174-5382

| Thread Class: |
|---|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.500 inches |
| Fastener Length: |
| 1.500 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.312 inches and 0.313 inches |
| Head Height: |
| Between 0.185 inches and 0.190 inches |
| Hole Diameter: |
| Between 0.044 inches and 0.050 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.1900 inches |
| Width Across Flats: |
| Between 0.1562 inches and 0.1587 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Minimum Yield Strength: |
| 1600 pounds per square inch |
| Hole Configuration Style: |
| Round internal hexagon |
| Material: |
| Stainless steel |
| Material Specification: |
| Ff-s-86 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Ff-s-86 federal specification single treatment response |
| Thread Series Designator: |
| |

Unf

NSN 5305-01-174-5382

Socket Head Cap Screw - Page 2 of 2



Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0