## NSN 5305-01-175-0609

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-175-0609 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.337 inches and 0.387 inches **Fastener Length:** Between 0.534 inches and 0.564 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.177 inches and 0.197 inches Thready Qty Per Inch (tpi): 32 **Surface Finish:** 32.0 microinches threads **Special Features:** Internal drive ribbed Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas1578 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-175-0609

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0