## NSN 5305-01-175-3643

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-175-3643



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.262 inches and 0.375 inches Fastener Length: Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches Locking Feature: Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch Material: Steel fastener Surface Treatment: Cadmium fastener and chromate fastener Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response fastener **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life:

N/a

## NSN 5305-01-175-3643

Socket Head Cap Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0