

View Online at <https://aerobasegroup.com/nsn/5305-01-175-3673>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.474 inches and 0.510 inches

Fastener Length:

Between 1.448 inches and 1.528 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.5018 inches and 0.5066 inches

Grip Diameter:

Between 0.2487 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Grip Length:

Between 0.938 inches and 0.954 inches

Width Across Flats:

0.250 inches

Thready Qty Per Inch (tpi):

28

Countersink Angle:

100.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.318 inches first hole and 1.324 inches first hole

Surface Finish:

63.0 microinches grip

Special Features:

Includes nut

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0