

View Online at <https://aerobasegroup.com/nsn/5305-01-175-6938>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.477 inches and 0.636 inches

**Fastener Length:**

Between 1.047 inches and 1.067 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.360 inches and 0.404 inches

**Internal Drive Style:**

Hexagon

**End Application:**

Cruise missile

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

Between 0.1562 inches and 0.1587 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Three slots 0.040 in. Wide by 0.029 in. Deep along the longitudinal axis and 120 degrees apart; thread to be double lead

**Material:**

Iron alloy 660

**Material Specification:**

Ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0