# NSN 5305-01-175-7554

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-175-7554



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.589 inches and 0.682 inches

## Fastener Length:

Between 0.719 inches and 0.750 inches

### Head Style:

Flat countersunk

## Head Diameter:

Between 0.282 inches and 0.332 inches

## Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.164 inches

# Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

125000 pounds per square inch

### Countersink Angle:

Between 99.0 degrees and 101.0 degrees

### Screw Material:

Steel comp 4037 or steel comp 8630

### Screw Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

### Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## Color:

Black

## **Thread Series Designator:**

Unjc

## **Specification Data:**

80205-nas514 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5305-01-175-7554

Machine Screw - Page 2 of 2

**Fiig:** A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

