NSN 5305-01-176-0884

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-176-0884

The Committee of the Co
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.511 inches and 0.625 inches
Fastener Length:
Between 0.594 inches and 0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.313 inches
Head Height:
Between 0.185 inches and 0.190 inches
Locking Feature:
Patch threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unc
Specification Or Standard:
6 type

NSN 5305-01-176-0884

Socket Head Cap Screw - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0