
NSN 5305-01-176-7383

Close Tolerance Screw - Page 1 of 2

3a

32

N/a





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.338 inches and 0.388 inches Fastener Length: Between 0.598 inches and 0.628 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.258 inches and 0.305 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1581 professional/industrial association standard Shelf Life:

NSN 5305-01-176-7383

Close Tolerance Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0