## NSN 5305-01-177-1793

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-177-1793 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.164 inches and 0.265 inches **Fastener Length:** Between 0.235 inches and 0.265 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.140 inches and 0.150 inches **Locking Feature:** Patch threads **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1216 professional/industrial association standard Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-177-1793

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0