NSN 5305-01-177-1798

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-177-1798 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** Between 1.710 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch **Hole Configuration Style:** Round internal hexagon Color: Black Material: Steel **Surface Treatment:**

Oxide

NSN 5305-01-177-1798

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Mil-c-13924 cl 1 military specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.