
## NSN 5305-01-177-1813

Close Tolerance Screw - Page 1 of 2





## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.338 inches and 0.388 inches Fastener Length: Between 1.160 inches and 1.190 inches **Head Style:** Flat countersunk **Head Diameter:** 0.3813 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches Internal Drive Style: Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Special Features:** Internal drive ribbed Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard

Shelf Life:

N/a

## Unit Of Measure:

---

## NSN 5305-01-177-1813

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

