## NSN 5305-01-177-2567

No

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-177-2567 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 0.750 inches **Head Diameter:** 0.437 inches **Head Height:** 0.250 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 82.0 degrees Material: Steel comp 303 **Material Specification:** Astm-a-581 assn standard single material response or astm-a-582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072-e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

## NSN 5305-01-177-2567

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072-e300 spec.