NSN 5305-01-177-5894



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-177-5894 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.400 inches **Fastener Length:** Between 2.740 inches and 2.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.848 inches and 0.925 inches **Shoulder Diameter:** 0.622 inches first shoulder and 0.623 inches first shoulder **Shoulder Length:** 2.176 inches first shoulder and 2.186 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 2.617 inches first hole and 2.627 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-177-5894 Shoulder Screw - Page 2 of 2



Fiig:

A003b0