## NSN 5305-01-177-9729

**Unit Of Measure:** 

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-177-9729 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.146 inches and 1.248 inches **Fastener Length:** Between 1.335 inches and 1.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.359 inches and 0.411 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.125 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Special Features:** Colorblack Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384 **Material Specification:** 66 federal standard all material responses or astm a493 assn standard single material response **Surface Treatment:** Oxide **Thread Series Designator:** Unrf Shelf Life: N/a

## NSN 5305-01-177-9729

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0