NSN 5305-01-178-2065

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-178-2065

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.273 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches Head Style: Fillister Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch Screw Material:
Thread Direction: Right-hand Thread Length: Between 0.273 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches Head Style: Fillister Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Right-hand Thread Length: Between 0.273 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches Head Style: Fillister Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Thread Length: Between 0.273 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches Head Style: Fillister Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Between 0.273 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches Head Style: Fillister Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Fastener Length: Between 0.344 inches and 0.375 inches Head Style: Fillister Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Between 0.344 inches and 0.375 inches Head Style: Fillister Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Head Style: Fillister Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Fillister Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Head Diameter: Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Between 0.389 inches and 0.414 inches Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Head Height: Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Between 0.161 inches and 0.170 inches Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Hole Diameter: Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Between 0.061 inches and 0.066 inches Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Internal Drive Style: Slot Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Thread Diameter: 0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
0.250 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Hole Quantity: 1 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch
28 Min. Tensile Strength (psi): 80000 pounds per square inch
Min. Tensile Strength (psi): 80000 pounds per square inch
80000 pounds per square inch
Screw Material:
Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se
Screw Material Specification:
66 federal standard all material responses
Screw Surface Treatment:
Passivate
Head Hole Configuration Style:
Round
Thread Series Designator:
Unf
Specification Or Standard:
1 type and 5s style
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-178-2065

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0