NSN 5305-01-178-2066

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-178-2066

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.839 inches and 0.875 inches
Fastener Length:
0.875 inches
Head Style:
Flat chamfer
Head Diameter:
0.140 inches
Head Height:
Between 0.083 inches and 0.086 inches
Locking Feature:
Patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.086 inches
Width Across Flats:
0.078 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Specification Or Standard:
6 type
Shelf Life:
N/a

NSN 5305-01-178-2066

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0