

View Online at <https://aerobasegroup.com/nsn/5305-01-178-3348>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.107 inches and 0.163 inches

Fastener Length:

Between 0.157 inches and 0.188 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.105 inches and 0.119 inches

Internal Drive Style:

Slot

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Countersink Angle:

100.0 degrees

Screw Material:

Copper alloy 230 or copper alloy 377 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 360 or copper alloy 377 or copper alloy 353 or copper alloy 270 or copper alloy 274 or copper alloy 482 or copper alloy 485 or copper alloy 210 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 240 or copper alloy 220

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Jan-f-495 type 3 mfr ref single treatment response

Color:

Black

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0