NSN 5305-01-178-3688

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-178-3688 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.938 inches and 2.000 inches **Fastener Length:** 2.000 inches **Head Style:** Flat chamfer **Head Diameter:** 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: 0.141 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life:

N/a

NSN 5305-01-178-3688

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0