## NSN 5305-01-178-7408

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-178-7408 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.346 inches and 0.438 inches **Fastener Length:** Between 0.408 inches and 0.438 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch **Hole Configuration Style:** Round internal hexagon **Special Features:** Finish color black Material: Steel **Surface Treatment:** 

Cadmium and chromate

## NSN 5305-01-178-7408

Socket Head Cap Screw - Page 2 of 2



## **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:** 

Unrf

**Specification Data:** 

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0