

NSN 5305-01-178-7411 Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-178-7411 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.291 inches and 0.341 inches **Fastener Length:** Between 3.051 inches and 3.081 inches

**Head Style:** 

Flat countersunk

**Head Diameter:** 

Between 0.449 inches and 0.507 inches

**Grip Diameter:** 

Between 0.2485 inches and 0.2495 inches

**Internal Drive Style:** 

Offset cruciform (torque set)

**Thread Diameter:** 

0.250 inches

**Grip Length:** 

Between 2.740 inches and 2.760 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Iron alloy 660

**Material Specification:** 

Ams 5737 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas1154 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-178-7411

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0