## NSN 5305-01-179-0906

Machine Screw - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5305-01-179-0906

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.376 inches and 0.451 inches
Fastener Length:
Between 0.579 inches and 0.624 inches
Head Style:
Flat countersunk
Head Diameter:
0.315 inches
Internal Drive Style:
Cross recess type ii
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Steel
Screw Material Specification:
Ams 6322 assn standard single material response
Bearing Surface Of Head Surface Treatment:
Cadmium
Head Surface Treatment:
Cadmium
Screw Surface Treatment:
Cadmium
Shank Surface Treatment:
Cadmium
Bearing Surface Of Head Surface Treatment Specification:
Qq-p-416, type 2, class 2, except baking required after plating federal specification single treatment response
Head Surface Treatment Specification:
Qq-p-416, type 2, class 2, except baking required after plating federal specification single treatment response
Screw Surface Treatment Specification:
Qq-p-416, type 2 class 2, except baking required after plating federal specification single treatment response
Shank Surface Treatment Specification:
Qq-p-416, typr 2 class 2, except baking required after plating federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5305-01-179-0906

Machine Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0