NSN 5305-01-179-3353

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-179-3353



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.266 inches and 0.281 inches

Fastener Length:

Between 0.485 inches and 0.515 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.297 inches and 0.327 inches

Head Height:

Between 0.085 inches and 0.115 inches

Shoulder Diameter:

0.181 inches first shoulder and 0.187 inches first shoulder

Shoulder Length:

0.047 inches first shoulder and 0.078 inches first shoulder

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Shoulder Shape:

Round first shoulder

Material:

Steel comp 303 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 or steel comp 321 or steel comp 347

Material Specification:

Astm a-582 assn standard 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-s-763 federal specification 7th material response or qq-s-763 federal specification 8th m

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

28009-16600391 manufacturers specification control

Shelf Life:

N/a

Init Of Massura

NSN 5305-01-179-3353

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

