

View Online at <https://aerobasegroup.com/nsn/5305-01-179-3354>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.198 inches and 0.238 inches

Fastener Length:

Between 0.233 inches and 0.243 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.235 inches and 0.265 inches

Head Height:

Between 0.052 inches and 0.072 inches

Shoulder Diameter:

0.183 inches first shoulder and 0.185 inches first shoulder

Shoulder Length:

0.025 inches first shoulder and 0.035 inches first shoulder

Internal Drive Style:

Slot

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Shoulder Shape:

Round first shoulder

Material:

Steel comp 303 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 or steel comp 317 or steel comp 321

Material Specification:

Astm a-582 assn standard 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-s-763 federal specification 7th material response or qq-s-763 federal specification 8th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A003b0