NSN 5305-01-179-4409

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-179-4409 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.380 inches and 0.410 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Round extended washer **Head Diameter:** 0.375 inches **Head Height:** Between 0.089 inches and 0.099 inches **Extended Washer Diameter:** 0.437 inches **Extended Washer Thickness:** Between 0.025 inches and 0.030 inches **Locking Feature:** Strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 8630 **Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unjf

, د د

Shelf Life:

N/a

NSN 5305-01-179-4409

Socket Head Cap Screw - Page 2 of 2



	• -		
In	ıŧ	()t	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.