NSN 5305-01-179-5256

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-179-5256 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.917 inches and 1.047 inches **Fastener Length:** Between 1.234 inches and 1.281 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.720 inches and 0.781 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.219 inches and 0.221 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 70000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel comp 303 or steel comp 304 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Thread Series Designator: Unf **Specification Or Standard:** 4 type Shelf Life: N/a

NSN 5305-01-179-5256

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0