## NSN 5305-01-180-8682



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-180-8682 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.166 inches and 0.178 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.171 inches and 0.199 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.099 inches Thready Qty Per Inch (tpi): 48 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Product Name:** Navy special project **Screw Material:** Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316 or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A500d0