NSN 5305-01-180-8696

Close Tolerance Screw - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5305-01-160-6696
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.337 inches and 0.387 inches
Fastener Length:
Between 0.472 inches and 0.502 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.258 inches and 0.305 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Special Features:
Internal drive ribbed
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

Specification Data: 80205-nas1581 professional/industrial association standard

NSN 5305-01-180-8696

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0