

View Online at <https://aerobasegroup.com/nsn/5305-01-181-0806>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.366 inches

Fastener Length:

0.936 inches

Head Style:

Flat countersunk

Head Diameter:

0.429 inches

Shoulder Diameter:

0.3188 inches first shoulder and 0.3200 inches first shoulder

Shoulder Length:

0.540 inches first shoulder and 0.550 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Thread Qty Per Inch (tpi):

28

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.828 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Titanium alloy

Material Specification:

Mil-t-9047, cond anld military specification single material response

Surface Treatment:

Aluminum head

Surface Treatment Specification:

Ps13143 ty1 cl 3, fscm 76301 mfr ref single treatment response grip

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-t-9047 spec.