NSN 5305-01-181-5031

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-181-5031 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.380 inches and 0.447 inches **Fastener Length:** Between 0.765 inches and 0.812 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.338 inches and 0.381 inches **Head Height:** Between 0.032 inches and 0.034 inches **Shoulder Diameter:** 0.218 inches first shoulder **Shoulder Length:** 0.365 inches first shoulder and 0.385 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one o-ring Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-181-5031 Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A003b0