NSN 5305-01-181-7465

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-181-7465 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.156 inches **Fastener Length:** Between 0.451 inches and 0.466 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.105 inches and 0.110 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.194 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Quad lead thread Material: Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 304 or steel comp 304l **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-181-7465

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0