Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-182-4091

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
Between 0.969 inches and 1.000 inches
Head Style:
Fillister
Head Diameter:
Between 0.250 inches and 0.270 inches
Head Height:
Between 0.106 inches and 0.113 inches
Hole Diameter:
0.046 inches
First Diameter From Head:
Between 0.125 inches and 0.131 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.625 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Hole Quantity:
1
Ноје Туре:
Drilled
Thready Qty Per Inch (tpi):
32
Hole Configuration Style:
Round
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0