NSN 5305-01-182-7666

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-182-7666



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.359 inches and 0.453 inches

Fastener Length:

Between 0.969 inches and 1.031 inches

Head Style:

Round extended washer

Head Diameter:

0.375 inches

Head Height:

Between 0.089 inches and 0.099 inches

Extended Washer Diameter:

0.437 inches

Extended Washer Thickness:

Between 0.020 inches and 0.030 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Screw Material:

Steel comp 8630 or steel comp 4037

Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, ty2, cl3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5305-01-182-7666

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

