## NSN 5305-01-182-8351

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-182-8351 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.476 inches and 0.526 inches **Fastener Length:** Between 1.174 inches and 1.204 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.5780 inches and 0.6335 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.3125 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Internal drive ribbed Material: Titanium alloy **Material Specification:** Ams 4967, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-182-8351

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0