NSN 5305-01-183-3280



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-183-3280 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.359 inches **Fastener Length:** 0.359 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or ams 6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas5902 professional/industrial association standard Shelf Life:

Demilitarization:No **Fiig:**

Unit Of Measure:

A500d0

N/a

NSN 5305-01-183-3280

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.