

View Online at <https://aerobasegroup.com/nsn/5305-01-183-3284>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.880 inches

**Fastener Length:**

Between 0.850 inches and 0.880 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.105 inches and 0.120 inches

**Width Between Flats:**

Between 0.305 inches and 0.313 inches

**Internal Drive Style:**

Tri-wing recess

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Screw Material:**

Steel comp 4340 or steel comp 8740

**Screw Material Specification:**

Mil-s-5000 military specification 1st material response or ams 6322 assn standard 2nd material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas5903 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5000 spec.