NSN 5305-01-183-3293

Machine Screw - Page 1 of 2

Fiig: A500d0



View Online at https://aerobasegroup.com/nsn/5305-01-183-3293 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.562 inches **Fastener Length:** Between 0.532 inches and 0.562 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.313 inches **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or ams 6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas5903 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-01-183-3293

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.