NSN 5305-01-183-4023

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-183-4023 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.189 inches and 0.199 inches **Fastener Length:** Between 0.715 inches and 0.745 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.346 inches and 0.376 inches **Head Height:** Between 0.115 inches and 0.135 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** Between 0.188 inches and 0.250 inches **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1406 inches and 0.1426 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp 304 stand-off **Material Specification:** Qq-w-423, comp fs302, cond b federal specification single material response spring **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-183-4023

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0