NSN 5305-01-183-5539

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-183-5539 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.107 inches and 0.198 inches **Fastener Length:** Between 0.178 inches and 0.198 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1253 inches and 0.1270 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch **Surface Finish:** 32.0 microinches bearing surface of head **Special Features:** Three external slots 0.030-0.034 in. Dia., 0.148-0.168 in. Lg; point reamed to accept plug; 0.143 in. Dia. Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-183-5539

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0