## NSN 5305-01-183-5837

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-183-5837 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.423 inches and 0.515 inches **Fastener Length:** Between 0.485 inches and 0.515 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1216 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0